

Masking Tape Specification (TDS)

CP077

Property	Unit	Condition	Value
Total thickness	mm		0.145 ±0.015mm
Steel Adhesion	g/inch	Min.	450
↳	N/100mm		17.37
↳	OZ/IN		15.87
Initial tack	mm	Max.	40
Holding power	Hours	Min	30
Tensile Strength	Kg/15mm	Min.	4.6
↳	N/100mm		300.74
↳	IB/IN		17.17
Elongation	%	Min.	6
Temp. resistance to stainless steel	°C	Max.	95
↳	°F		203
Waterproof property			X
Adhesive type			Solvent based natural Rubber
Backing			Crepe paper
Color			Orange

Notes · 주의사항

적용:내열이 있고 고성능 테이프로 건축 도장 및 산업용에 적합.

Application: single-sided, unidirectional fiberglass-reinforced tape for securing heavy, rigid goods (e.g. refrigerators) and reinforcing boxes.

실리콘작업에 사용.

1. 직사광선을 피해서 보관하여 주시고, 23°C 이상, 습도 50%이상 환경은 피해 주십시오.

1. Store away from direct sunlight and avoid environments above 23 °C or 50 % relative humidity.

2. 유통기한: 완제품인 경우 6개월 초과 하지 말아 주십시오.

2. Shelf life: use finished product within 6 months.

Source: SMC technical data sheet (SMC-TDS-CP077.docx). Values as published by SMC Co., Ltd.; specifications may change without notice.