

Masking Tape Specification (TDS)

GS501 Filament

Property	Unit	Acceptable	Value
Total thickness	mm		0.148
Backing thickness			58g/m2
Adhesion to steel	N/25mm		20
Tensile Strength	N/25mm		1250
Elongation	%	Min.	4.5
Temp. resistance to stainless steel	°C	Max.	60
↳	Min		30
Adhesive type			Synthetic rubber and resins
Backing			Glass fibre reinforced+Bopp film
Color			White

Notes · 주의사항

적용: 무겁고 단단한 물품(예:냉장고) 및 상자 강화에 적합한 고정력 단방향 섬유 유리 강화 단면 테이프로 적합.

Application: single-sided, unidirectional fiberglass-reinforced tape for securing heavy, rigid goods (e.g. refrigerators) and reinforcing boxes.

1. 직사광선을 피해서 보관하여 주시고, 23°C 이상, 습도 50%이상 환경은 피해 주십시오.

1. Store away from direct sunlight and avoid environments above 23 °C or 50 % relative humidity.

2. 유통기한: 완제품인 경우 6개월 초과 하지 말아 주십시오.

2. Shelf life: use finished product within 6 months.

Source: SMC technical data sheet (SMC-TDS-GS501.docx). Values as published by SMC Co., Ltd.; specifications may change without notice.